Specification for proposed path at Waterford

Location (refer to plan)

Red line - Proposed new route linking new development to the village of Bengeo (c. 600m)

Blue line - Potential path extension to Waterford Heath car park (c. 160m)

Path specification

Levelled and compacted earth surface to create a natural route winding through the trees.

Trees and shrubs will be removed to create a path width of 1.5m along the proposed line. All stumps will be removed.

Path condition will be reviewed after 12 months. Type 1 and granite dust surface will be laid on areas requiring improvement.

Gates, fencing and signage

Entrance Kissing gate (Locations A, C, F)

Medium Mobility Wooden kissing gate (H-1.2m, W- 2.75m) BS5709:2006 specification

Hoggin or Type 1 material to be placed in gateway to provide firm and level surface



Safety Fencing (Location B)

1.2m high stock proof fencing with two strands of plain wire



Low Wooden fence

Diamond rail fencing (h-0.4m). This will encourage people to walk around the grassland meadow area and join the existing path.



Wooden Pedestrian gate (Location E)

Timber Pedestrian gate (H -1.2m, W -1.7m) BS5709:2006 specification



Signs (Locations A, C and F)

Entrance signs to be erected at all entrances to new path. These will include the path name. Specification to be agreed

Post-Construction Maintenance

The footpath and ancillary infrastructure will be subject to monitoring and maintenance where appropriate for a period of three years upon completion of the engineering works.